



FAX_LAB 126

PLAIN-PAPER INK-JET FAX

HANDY, EASY TO USE
Navigation key for easy scroll and quick selection of the menu items.

RELIABLE ANSWERPHONE
The answerphone memory maintains safe your documents when mains is off.

UNFAILING CONFIDENTIALITY
Fax_Lab 126 does not retain any trace of the document once printed thanks to its proprietary ink-jet technology.

FAX	7 sec
ANSWER PHONE	15 min
SMS*	
COPIER	UP TO 9
MEMORY	UP TO 30 PAGES
PLAIN PAPER	UP TO 40 SHEETS
CARTRIDGE	FJ51

FAX_LAB 126

FAX	Printing method	Ink-jet on plain paper
	Compatibility	Group 3
	Transmission speed	7 seconds at 14,400 bps
	Compression method	MH, MR, MMR with Error Correction Mode (ECM)
	Document format	A4
	Automatic document feeder	5 pages
	Paper tray	40-sheets
	Memory (pages)	Up to 30 (ITU-TS sample text, MH compression, 3.8% coverage)
	Scan resolution	200 x 200 dpi
	Contrast control	Manual
TELEPHONE	Greyscale	64 levels
	One-touch/abbreviated dialling	10/50 numbers
TELEPHONE	Functions	Broadcasting from memory to up to 10 numbers Substitute reception Automatic fax/telephone and answering machine/fax switching Silent reception
	Functions	Hands-free dialling Caller identification Conversation on hold
TELEPHONE	Answerphone	Up to 15-minute voice message recording time Unlimited message storage time Call screening Personal access code Remote access
	Functions	SMS writing (characters associated with numeric keypad) SMS transmission to fixed and mobile numbers Storage of up to 30 incoming SMS Printout of received SMS
COPIER	Copying	Single page
	Zoom	50%, 70%, 100%, 140%, 200%
OTHER CHARACTERISTICS	Multiple copies	Up to 9 copies
	Display	2 lines x 16 characters
	Consumption	3 W in stand-by, 25 W max
	Starter cartridge	Included
	Consumable cartridge	FJ 51, code B0494, capacity 450 pages (ITU-TS sample text, MH compression, 3.8% coverage)
Dimensions (LxWxH)	340x235x273 mm	
Weight	2.5 Kg	

* feature may not be available in some countries.

Compliant with European RoHS environment regulations.

www.olivetti.com

Performance rates refer to use in optimal conditions. With the right to change technical specifications. 25933